



► Feature:

1. Built-in high-quality crossover, precisely tuned for accurate sound reproduction.
2. Multi-point hanging design allows both horizontal and vertical installation to meet various mounting needs.
3. Bottom pole socket design enables easy connection with subwoofers.
4. Bottom input terminal for convenient stage monitor connections.
5. Ergonomic arc-shaped top handle for easy transportation.
6. Professional 55° monitor angle design, allowing flexible use as a stage monitor or full-range speaker.

► Specification:

1. LF Driver: 1 × 15" (75mm voice coil, 190mm ferrite magnet)
2. HF Driver: 1 × 3" (75mm voice coil, 90mm ferrite magnet)
3. Frequency Response: 50Hz – 20KHz
4. Sensitivity (1W/1M): 98 dB
5. Maximum SPL: 125 dB
6. Rated Power: 600 Watts
7. Peak Power: 1200 Watts
8. Nominal Impedance: 8Ω
9. Cabinet Material: Birch plywood
10. Acoustic Design: Arc-shaped front air guide
11. Finish: Eco-friendly black water-based textured paint
12. Grille: 1.5T black painted steel grille (optional dust-proof fabric available)
13. Mounting Options: Multi-point suspension / wall mount / tripod stand
14. Connectors: Parallel 3 × Speakon NL4 + 2 × binding posts + series/parallel switch
15. Dimensions (H × W × D): 700 × 460 × 480 mm
16. Coverage Angle: H 90° × V 60°
17. Net Weight: 31 kg