



### ► Feature:

- Dynamic cardioid microphone design for clear and accurate voice pickup with excellent background noise rejection.
- Wide frequency response range of 40Hz–20kHz ensures natural and detailed sound reproduction.
- Built-in spherical windscreen and pop filter effectively reduce wind noise and plosive sounds for cleaner audio performance.
- High-sensitivity pickup element delivers strong and stable audio signal transmission.
- Equipped with professional XLR connector for reliable and secure audio connection.
- 350Ω nominal impedance design provides excellent compatibility with professional audio equipment.
- Supplied with a shock-resistant stand to minimize vibration and handling noise during use.
- 200mm gooseneck design allows flexible and convenient microphone positioning.
- Comes with a 5-meter cable for easy installation and extended operating distance.
- Suitable for conference rooms, podiums, broadcasting, public speaking, and professional sound reinforcement applications.

### ► Specification:

| Specification                            | Description                                                                     |
|------------------------------------------|---------------------------------------------------------------------------------|
| Microphone Type                          | Dynamic Microphone (Cardioid)                                                   |
| Frequency Response Range                 | 40 – 20,000 Hz                                                                  |
| Polar Pattern                            | Cardioid                                                                        |
| Sensitivity (Free Field, No Load, 1 kHz) | 2.8 mV/Pa at 1 kHz = -51 dB (0 dB = 1 V/Pa) =<br>-71 dB (0 dB = 1 V/ $\mu$ bar) |
| Nominal Impedance                        | 350 $\Omega$                                                                    |
| Minimum Terminating Impedance            | 1 k $\Omega$                                                                    |
| Connector                                | XLR                                                                             |
| Gooseneck Length                         | 200 mm                                                                          |
| Cable Length                             | 5 m                                                                             |
| Windscreen & Pop Filter                  | Built-in spherical windscreen and pop filter                                    |
| Stand                                    | Supplied with shock-resistant stand (included)                                  |