



Feature:

1. Adopt U-band adjustable frequency solution to improve the flexibility of use
2. Adopt UHF high-performance integrated circuit design, stable and reliable
3. Visual high-definition screen display, which can display working frequency, channel, battery power, RF/AF signal and other
4. contents
5. Metal hand-held texture, ergonomic design, streamlined appearance processing, better fit the hand curve, comfortable grip
6. Each channel has the function of independent manual selection of spectrum frequency points
7. One-key infrared frequency setting, multiple transmitters can be selected and interchanged, simple operation
8. Digital frequency locking technology, super anti-interference ability

Specification:

Parameter	Specification
RF Range	640.00-690.00MHz
Bandwidth	35 — 20KHz
Modulation Mode	FM Frequency Modulation
Sensitivity	6.3 dBuV /-100 dBm
Frequency Matching Mode	Infrared Automatic Frequency Matching
Number of Channels	200 Channels
Noise Suppression Mode	Automatic Noise Detection and Digital ID Code
Deviation	45KHz
Dynamic Range	110dB
Frequency Response	30Hz-20KHz
Antenna Interface	BNC/50Ω × 2
Output Interface	1 × Unbalanced φ6.35mm Interface
	2 × Independent Balanced XLR Interfaces
Power Supply	DC 12V 600mA
Dimensions (L×D×H)	420×180×45mm