



Feature:

- 4x4 fast matrix switching
- Video transmission rate up to 18Gbps, supporting 4K@60 4:4:4.
- HDR Support: HDR10, HLG, Dolby Vision
- All output ports support audio de-embedding.
- Output support automatic downsampling.
- Audio De-embedding: SPDIF Output
- Supports CEC control between source and sink.
- Built-in EDID, EDID learning, and custom EDID functions.
- Can be controlled via front-panel buttons, IR, RS-232, or TCP/IP.
- Built-in 17 EDID presets covering 1080p@60Hz to 4K@60Hz 4:4:4 (8-bit, HDR 10/12-bit) with 2CH PCM, 5.1CH, and 7.1CH DTS/Dolby/Dolby audio.

Specification:

Parameter	Specification
Model	T3-JZ0404
Input Signal	4 x HDMI
Input Connector	Type A 19-pin female
Input Resolution	Up to 4K@60Hz
Input Color Space	4:4:4
Output Signal	4 x HDMI
Output Connector	Type A 19-pin female
Output Resolution	Up to 4K@60Hz
Output Color Space	4:4:4
Audio	LPCM 7.1 audio, Dolby Atmos®, Dolby® TrueHD, Dolby Digital® Plus, DTS:X™, and DTS-HD® Master Audio™
HDMI Standard	2
HDCP	HDCP 2.2 and backward compatible
Audio Frequency Response	20Hz–20kHz
THD+N	<0.05%
SNR	>80dB (analog), >90dB (digital)
Crosstalk Isolation	<-80dB (analog), <-70dB (digital)
Control Methods	RS-232, IR, TCP/IP (web), buttons
Operating Temperature	-5°C to +55°C
Storage Temperature	-20°C to +70°C
Relative Humidity	0% to 90%
Power Supply	DC 24V, 1.25A
Power Consumption	1.2W
Dimensions (W x H x D)	436.4 mm x 44 mm x 160 mm
Net Weight	1.76 kg